

Technical product information

Pipe Lubricant STONEWARE blue for stoneware pipes

Pipe Lubricant STONEWARE blue is a blue paste and used especially for easy assembly of stoneware pipes and pit parts in sewerage systems.

Pipe Lubricant STONEWARE blue has to be applied with a brush or gloves onto the concrete gliding plane in the socket or on the spigot end of the pipe. We recommend applying **Pipe Lubricant STONEWARE blue** in sufficient quantities just shortly before the installation of the pipes in order to prevent the drying-up of the lubrication film. The application of **STONEWARE blue** is possible in a temperature range of -10° C up to +50° C at all weather conditions, even with wet pipes.

Due to the usage of natural and mineral based raw materials **STONEWARE blue** is environmentally problem free and rapidly bio-degradable.

Pipe Lubricant STONEWARE blue is available in buckets of 1 kg, 3 kg, 5 kg und 10 kg. Special packaging on request.

Technical data

Consistency: paste
 Colour: blue
 Working temperature : - 10° C - + 50° C

We recommend to store **pipe lubricant STONEWARE blue** between + 5°C and + 25°C in closed buckets.

With one kg of **Pipe Lubricant STONEWARE blue** the following number of pipes can be embedded:

Pipes (DN):	300	400	500	600	700	800	900	1000	1200
Number:	12	9	7	5	5	4	4	3	3

Pit-Rings (DN):	1000	1200	1500
Number:	7	3	2

Theses information corresponds with the actual technical standings. Subject to change without notice. All data can not be taken as warranted characteristics for each individual case. They do not absolve the consumer from own verifications. Additional data on request.